

OWNER'S MANUAL **LED MONITOR**(LED Monitor*)

* LG LED Monitor applies LCD screen with LED backlights. Please read this manual carefully before operating your set and retain it for future reference.

32UQ750

www.lg.com

Copyright © 2018 LG Electronics Inc. All Rights Reserved.

TABLE OF CONTENTS

OPEN SOURCE SOFTWARE NOTICE INFORMATION	
ASSEMBLING AND PREPARING	3
USING THE MONITOR	. 10
USER SETTINGS	. 12
TROUBLESHOOTING	. 23
PRODUCT SPECIFICATION	. 25

LICENSE2

LICENSE

Each model has different licenses. Visit www.lg.com for more information on the license.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



The SuperSpeed USB Trident logo is a registered trademark of USB Implementers Forum, Inc.

↓↓↓ MaxxAudio[®]

MaxxAudio and additional MAXX trademarks are trademarks and/ or registered trademarks of Waves Audio Ltd.

* USB Type-C[™] and USB-C[™] are trademarks of USB Implementers Forum.

OPEN SOURCE SOFTWARE NOTICE INFORMA-TION

To obtain the source code that is contained in this product, under GPL, LGPL, MPL, and other open source licenses that have the obligation to disclose source code, and to access all referred license terms, copyright notices and other relevant documents, please visit https://opensource.lge.com.

LG Electronics will also provide open source code to you on CD-ROM for a charge covering the cost of performing such distribution (such as the cost of media, shipping, and handling) upon email request to opensource@lge.com. This offer is valid to anyone in receipt of this information for a period of three years after our last shipment of this product.

ASSEMBLING AND PREPARING

AUTION

- Always use genuine LG components to ensure safety and product performance.
- The product warranty will not cover damage or injury caused by the use of unauthorized components.
- It is recommended to use the supplied components.
- If you use generic cables not certified by LG, the screen may not display or there may be image problems.
- Illustrations in this document represent typical procedures, so they may look different from the actual product.
- Do not apply foreign substances (oils, lubricants, etc.) to the screw parts when assembling the product. (Doing so may damage the product.)
- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this
 way will not be covered by the product warranty.
- Do not carry the monitor upside down by just holding the base. This may cause the monitor to fall off the stand and could result in personal injury.
- When lifting or moving the monitor, do not touch the monitor screen. The force applied to the monitor screen may cause damage to it.
- For wave pattern on appearance, unlike the general method of coating, it's applied to added glittering material in raw material. With no peeled-off appearance, it has good durability. Please use it with confidence because there is no problem in using the product at all.

NOTE

- · The components may look different from those illustrated here.
- Without prior notice, all product information and specifications contained in this manual are subject to change
 to improve the performance of the product.
- To purchase optional accessories, visit an electronics store or an online shopping site, or contact the retailer from which you purchased the product.
- The power cord provided may differ depending upon the region.

Supported Drivers and Software

You can download and install the latest version from the LGE website (www.lg.com).

Drivers and Software	Installation Priority
Monitor Driver	Recommended
OnScreen Control	Recommended
Dual Controller	Optional

Product and Button Description

How to Use the Joystick Button

You can easily control the functions of the monitor by pressing the joystick button or moving it left/right/up/ down with your finger.

Basic Functions

	٩	Power on	Press the joystick button once with your finger to turn on the monitor.
		Power off	Press and hold the joystick button once more than 5 seconds with your finger to turn off the monitor.
	◀/►	Volume control	You can control the volume by moving the joystick button left/right.

NOTE

• The joystick button is located at the bottom of the monitor.

Moving and Lifting the Monitor

When moving or lifting the monitor, follow these instructions to prevent the monitor from being scratched or damaged and to ensure safe transportation, regardless of its shape or size.

- Place the monitor in the original box or packing material before attempting to move it.
- Before moving or lifting the monitor, disconnect the power cord and all other cables.
- Hold the bottom and side of the monitor frame firmly. Do not hold the panel itself.
- When holding the monitor, the screen should face away from you to prevent it from being scratched.
- When transporting the monitor, do not expose the monitor to shock or excessive vibration.
- When moving the monitor, keep it upright and never turn the monitor on its side or tilt it sideways.





AUTION

- Avoid touching the monitor screen as much as possible.
 - This may result in damage to the screen or some of the pixels used to create images.
- If you use the monitor panel without the stand base, its joystick button may cause the monitor to become
 unstable and fall, resulting in damage to the monitor or human injury. In addition, this may cause the joystick
 button to malfunction.

Installing on a Table


• Lift the monitor and place it on the table in an upright position. Place the monitor at least 100 mm (3.94 inches) away from the wall to ensure sufficient ventilation.

100 mm 100 mm (3.94 inches) (3.94 inches) 100 mm (3.94 inches) 100 mm (3.94 inches)

- Unplug the power cord before moving or installing the monitor. There is risk of electric shock.
- Make sure to use the power cord that is provided in the product package and connect it to a grounded power outlet.
- If you need another power cord, please contact your local dealer or the nearest retail store.

Adjusting the Stand Height

- Place the monitor mounted on the stand base in an upright position. 1
- Handle the monitor with both hands for safety. 2



WARNING

• When adjusting the screen height, do not place your hand on the stand body to avoid injury to your fingers.

Adjusting the Angle

- Place the monitor mounted on the stand base in an upright position. 1
- Adjust the angle of the screen. 2

The angle of the screen can be adjusted forward or backward from -5° to 20° for a comfortable viewing experience.

WARNING

- To avoid injury to the fingers when adjusting the screen, do not hold the lower part of the monitor's frame as illustrated below.
- Be careful not to touch or press the screen area when adjusting the angle of the monitor.




NOTE

 The left or right side of the monitor head can be slightly rotated up or down (up to 3°). Adjust the horizontal level of the monitor head.

Monitor head

Pivot Feature

The pivot feature allows the monitor to rotate 90° clockwise.



WARNING

- To avoid scratching the stand base, make sure that when rotating the monitor using the pivot feature, the stand does not make contact with the monitor.
- 1 Raise the monitor to the maximum height.



2 Adjust the angle of the monitor in the direction of the arrow as shown in the figure.



3 Rotate the monitor clockwise as shown in the figure.



4 Complete the installation by rotating the monitor 90° as shown below.



NOTE


- Auto Pivot feature of the display is not supported.
- The screen can be rotated easily using the screen pivot shortcut key provided with your Windows operating
 system. Note that some Windows versions and some graphics card drivers may use different settings for the
 screen pivot key or may not support the pivot key at all.

Using the Kensington Lock

The connector for the Kensington security system is located at the bottom of the monitor.

For more information on installation and usage, refer to the Kensington lock owner's manual or visit the website at http://www.kensington.com.

Connect the monitor to a table using the Kensington security system cable.



NOTE

• The Kensington security system is optional. You can obtain optional accessories from most electronics stores.

Installing the Wall Mount Plate

This monitor meets the specifications for the wall mount plate or other compatible devices.


NOTE

ENGLISH

- The wall mount plate is sold separately.
- For more information on installation, refer to the wall mount plate's installation guide.
- Be careful not to apply too much force while mounting the wall mount plate as it may cause damage to the screen.
- Remove the stand before installing the monitor on a wall mount by performing the stand attachment in reverse.

Installing on the Wall

Install the monitor at least 100 mm (3.94 inches) away from the wall and leave about 100 mm (3.94 inches) of space at each side of the monitor to ensure sufficient ventilation. Detailed installation instructions can be obtained from your local retail store. Alternatively, please refer to the manual for how to install and set up a tilting wall mounting bracket.



To install the monitor to a wall, attach a wall mounting bracket (optional) to the back of the monitor. Make sure that the wall mounting bracket is securely fixed to the monitor and to the wall.

Wall Mount (mm)	100 x 100
Standard screw	M4 x L10
Number of screws	4
Wall Mount Plate (Optional)	LSW 149

NOTE

- A non-VESA standard screw may damage the product and cause the monitor to fall. LG Electronics is not liable for any accidents relating to the use of non-standard screws.
- The wall mount kit includes the installation guide and all necessary parts.
- The wall mounting bracket is optional. You can obtain optional accessories from your local dealer.
- The length of the screw may differ for each wall mounting bracket. If you use screws longer than the standard length, it may damage the inside of the product.
- · For more information, please refer to the user manual for the wall mounting bracket.

AUTION

- Unplug the power cord before moving or installing the monitor to avoid electric shock.
- Installing the monitor on the ceiling or on a slanted wall may result in the monitor falling off, which could lead to injury. Use an authorized LG wall mount and contact the local dealer or qualified personnel.
- Applying excessive force when tightening screws may cause damage to the monitor. Damage caused in this
 way will not be covered by the product warranty.
- Use the wall mounting bracket and screws that conform to VESA standards. Damage caused by the use or misuse of inappropriate components will not be covered by the product warranty.
- When measured from the back of the monitor, the length of each installed screw must be 8 mm (0.3 inches) or less.

USING THE MONITOR

Illustrations in this manual may differ from the actual product.

Press the joystick button, go to [Settings] \rightarrow [Input], and then select the input option.

ENGLISH

- Do not press the screen for a prolonged time. This may cause image distortion.
- Do not display a still image on the screen for a prolonged time. This may cause image retention. Use a PC screensaver if possible.
- When connecting the power cord to the outlet, use a grounded (3-hole) power strip or a grounded power outlet.
- The monitor may flicker when turned on in an area where the temperature is low. This is normal.
- Sometimes red, green, or blue spots may appear on the screen. This is normal.

Connecting to a PC

- This monitor supports the *Plug and Play feature.
- * Plug and Play: A feature that allows you to add a device to your computer without having to reconfigure anything or install any manual drivers.

HDMI Connection

Transmits digital video and audio signals from your PC to the monitor.

- Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- High-Speed HDMI[®]/[™] cable
- High-Speed $\mathrm{HDMI}^\circ\!/^{\mathrm{TM}}$ cable with Ethernet

DisplayPort Connection

Transmits digital video and audio signals from your PC to the monitor.

NOTE

- There may be no video or audio output depending on the DP (DisplayPort) version of the PC.
- If you are using a Mini DisplayPort output graphics card, use a Mini DP to DP (Mini DisplayPort to DisplayPort) cable or gender that supports DisplayPort1.4. (Sold separately)

USB-C connection

Transmits digital video and audio signals from your PC to the monitor.

NOTE

- PD(Power Delivery) and DP Alternate Mode(DP over USB-C) are supported via USB-C Port.
- · Features may not work properly depending on the connected device's specifications and the environment.
- USB-C port is not for the Monitor Power source but for a PC power source. Connect Adapter to supply power to the Monitor

Connecting AV Devices

HDMI Connection

HDMI transmits digital video and audio signals from your AV device to the monitor.

NOTE

- Using a DVI to HDMI / DP (DisplayPort) to HDMI cable may cause compatibility issues.
- Use a certified cable with the HDMI logo attached. If you do not use a certified HDMI cable, the screen may not display or a connection error may occur.
- Recommended HDMI cable types
- High-Speed HDMI[®]/[™] cable
- High-Speed HDMI°/™ cable with Ethernet

Connecting Peripherals

USB Device connection

The USB port on the product functions as a USB hub.

NOTE

- It is recommended you install all Windows Updates to keep your Windows up-to-date before connecting to the product for use.
- Peripheral devices are sold separately.
- A keyboard, mouse, or USB device can be connected to the USB port.
- The charging speed may vary depending on the device.
- To use USB Downstream port of monitor, user must connect Upstream port of monitor to Host PC using USB C-C
 or USB C-A cable.
- When the USB C-C cable is connected between Upstream port of monitor and Host PC, the Downstream port of monitor support USB 2.0 device.
- When the USB C-A cable is connected between Upstream port of monitor and Host PC, the Downstream port of
 monitor support USB 3.0 device.

However, Host PC must support USB 3.0 function.

AUTION

Cautions When Using a USB Device

- A USB device with an automatic recognition program installed, or that uses its own driver, may not be recognized.
- Some USB devices may not be supported or may not work properly.
- It is recommended to use a USB hub or hard disk drive with power supplied. (If the power supply is not
 adequate, the USB device may not be recognized properly.)

Headphones Connection

Connect peripherals to the monitor via the headphones port.

NOTE

- Peripheral devices are sold separately.
- Depending on the audio settings of the PC and external device, headphones and speaker functions may be limited.
- If you use angled earphones, it may cause a problem with connecting another external device to the monitor. Therefore, it is recommended to use straight earphones.





Angled

Straight (Recommend)

USER SETTINGS

NOTE

- Your monitor's OSD (On Screen Display) may differ slightly from that shown in this manual.
- When [Beep Guide] is activated, pressing the joystick button will take you to [Settings] right away.

Activating the Main Menu



Press the joystick button on the bottom of the monitor. Move the joystick up/down and left/right to set the options.

Press the joystick button once more to exit the main menu.

Button	Menu Status		Description
	Main menu disabled Main menu enabled		Enables the main menu.
			Exits the main menu. (Holding down the button more than 5 seconds to turn off the monitor. You can turn off the monitor this way at any time, including when the OSD is on.)
		Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the [Input] features.
		Main menu disabled	Adjusts the monitor volume level.
		Main menu enabled	Enters the [Settings] feature.
		Main menu disabled	Enters the [Accessibility] menu.
		Main menu enabled	Turns off the monitor.
		Main menu disabled	Enters the [Accessibility] menu.
	•	Main menu enabled	Enters the [Picture Mode] feature.

ENGLISH

Main Menu Features



Main Menu	Description		
[Input]	Sets input mode.		
[Power Off]	Turns off the monitor.		
[Settings]	Configures the screen settings.		
[Picture Mode]	Sets the picture mode.		
[Exit]	Exits the main menu.		

Menu Settings

- 1 To view the OSD menu, press the joystick button at the bottom of the monitor and then enter the [Settings].
- 2 Move the joystick up/down and left/right to set the options.
- 3 To return to the upper menu or set other menu items, move the joystick to ◀ or pressing (心) it.
- 4 If you want to exit the OSD menu, move the joystick to
 until you exit.





[Input]





[Sound]

[Quick Settings]

[Picture]

[General]

- **NOTE**
- 💽: On
- 🗩: Off

Quick Settings

[Settings] > [Quick Settings]	Description			
[Brightness]	A diwata the combu			
[Contrast]	Adjusts the contro	ast and brightness of the screen.		
[Volume]	Adjusts the volun	Adjusts the volume level.		
	NOTE			
	• You can adjust	• You can adjust [Mute] / [Unmute] by moving the joystick button to ▼ in the [Volume] menu.		
[Color Temp]	[Custom]	The user can adjust it to red, green, or blue by customization.		
	[Warm]	Sets the screen color to a reddish tone.		
	[Medium] Sets the screen color to between a red and blue tone. [Cool] Sets the screen color to a bluish tone.			
	[Manual] The user can fine-tune the color temperature.			
[Waves MaxxAudio®]	[0n]	MaxxAudio [®] by waves, recipient of a Technical GRAMMY Award [®] is a suite of studio-quality sound tools for a superior listening experience.		
	[Off]	Off] Disables the MaxxAudio function.		

Input

[Settings] > [Input]	Description			
[Input List]	Selects the input r	elects the input mode.		
[Aspect Ratio]	Adjusts the aspect	djusts the aspect ratio of the screen.		
	[Full Wide]	Full Wide] Displays the video in widescreen, regardless of the video signal input.		
	[Original]	ginal] Displays video according to the aspect ratio of the video signal input.		
	[Just Scan] The aspect ratio is not adjusted from the original.			

Picture

NOTE

• The [Picture Mode] that can be set depends on the Input signal.

[[Picture Mode] on SDR (Non HDR) signal]

[Settings] > [Picture]		Description		
[Picture Mode]	[Custom]	tom] Allows the user to adjust each element.		
	[Vivid]	Heightens contrast, brightness and sharpness to display vivid images.		
	[HDR Effect]	Optimizes the screen for high dynamic range.		
	[Reader]	Optimizes the screen for reading documents. You can brighten the screen in the OSD menu.		
	[Cinema]	a] Optimizes the screen to improve the visual effects of a video.		
	[sRGB] A standard RGB color space for the monitor and printer.			
	[DCI-P3]	Suitable for watching digital videos.		
	[FPS]	This mode is optimized for FPS games.		
	[RTS]	This mode is optimized for RTS Game.		
	[Color Weakness]	This mode is for users who cannot distinguish between red and green. It enables users with color weakness to easily distinguish between the two colors.		
	NOTE			
	• If the [Picture Mode] is c	hanged, the screen may flicker or the resolution of your PC screen may be affected.		

[[Picture Mode] on HDR signal]

[Settings] > [Picture]	Description		
[Picture Mode]	[Custom]	Allows the user to adjust each element.	
	[Vivid]	Optimized the screen for HDR vivid colors.	
	[Cinema]	Optimized the screen for HDR video.	
	[FPS]	This mode is optimized for FPS games.It is suitable for very dark FPS games.	
	[RTS]	This mode is optimized for RTS Game.	
	 NOTE HDR content may not display correctly depending on Windows 10 OS settings, please check HDR On/Off settings in Windows. When the HDR function is turned on, the characters or picture quality may be poor according to Graphic card performance. While the HDR function is on, screen flickering or cracking may occur when changing the monitor input or power on/off according to Graphic card performance. 		

[Settings] > [Picture]		Description		
[Picture Adjust]	[Brightness]	A diwata tha calay control		
	[Contrast]	Adjusts the color contra	ast and brightness of the screen.	
	[Sharpness]	Adjusts the sharpness of	of the screen.	
	[SUPER RESOLUTION+]	[High]	Optimizes the screen for crystal clear images. Best for high-definition video or games.	
		[Middle]	Optimizes the screen for comfortable viewing, with images at the middle level between the low and high modes. Best for UCC or SD videos.	
		[Low]	Optimizes the screen for smooth and natural images. Best for still images or images with less movement.	
		[0ff]	Displays in the most common setting. Disables [SUPER RESOLUTION+].	
		NOTE		
			ction to increase the sharpness of low resolution pictures, it is not recommended to use the function for normal text or for desktop icons. Doing so ssarily high sharpness.	
	[Black Level]	Sets the offset level (fo • Offset: as a reference	r HDMI only). for a video signal, this is the darkest color the monitor can display.	
		[High]	Keeps the current contrast ratio of the screen.	
		[Low]	Lowers the black levels and raises the white levels from the current contrast ratio of the screen.	
	[DFC]	Adjusts the brightness	automatically according to the screen.	

[Settings] > [Picture]		Description		
[Game Adjust]	[Response Time]	Sets a response time for displayed pictures based on the movement of the picture on the screen. For a normal environment, it is recommended that you use [Fast]. When there is a lot of motion, it is recommended that you use [Faster]. Setting to [Faster] may cause image sticking.		
		[Faster]	Sets the response time to faster.	
		[Fast]	Sets the response time to fast.	
		[Normal]	Sets the response time to normal.	
		[Off]	Does not use the response time improvement feature.	
	[Adaptive-Sync / VRR]	Provides seamless and natural images by synchronizing the vertical frequency of the input signal with that of the output signal.		
		AUTION		
		 Supported Interface: DisplayPort (Adaptive-Sync), HDMI (Variable Refresh Rate). Supported Graphic Card: A graphic card that supports NVIDIA's G-SYNC or AMD's FreeSync is necessary. 		
		Supported Version:	Make sure to update the graphic card to the latest driver.	
		For more information	on and requirement, refer to NVIDIA website (www.nvidia.com) and AMD website (www.amd.com).	
		[Extended] Enables wider frequency range of Adaptive-Sync/VRR function than basic mode. The screen may flicker during the game play.		
		[Basic]	Enables basic frequency range of Adaptive-Sync/VRR function.	
		[0ff]	Adaptive-Sync/VRR function off.	
	[Black Stabilizer]	Increasing the [Black S	ack contrast to have better visibility in dark scenes. Stabilizer] value brightens the low gray level area on the screen. (You can easily distinguish objects on dark game screens.) tabilizer] value darkens the low gray level area and increases the dynamic contrast on the screen.	

[Settings] > [Picture]		Description			
[Color Adjust]	[Gamma]	[Mode 1], [Mode 2], [Mode 3]	The higher the gamma value, the darker the image becomes. Likewise, the lower the gamma value, the lighter the image becomes.		
		[Mode 4]	If you do not need to	o adjust the gamma settings, select [Mode 4].	
	[Color Temp]	Set your own color tem	perature.		
		[Custom]	The user can custom	nize the red, green and blue color.	
		[Warm]	Sets the screen colo	r to a reddish tone.	
		[Medium]	Sets the screen colo	r to between a red and blue tone.	
		[Cool]	Sets the screen colo	r to a bluish tone.	
		[Manual]	The user can fine-tu	ne the color temperature.	
	[Red], [Green], [Blue]	You can customize the	picture color using [Re	ed], [Green], and [Blue] colors.	
	[Six Color]	Meets the user requirer	ments for colors by ad	justing the hue and saturation of the six colors (red, green, blue, cyan, magenta, and yellow) and then saving the settings.	
		[Hue]	Adjusts the tone of t	the screen colors.	
		[Saturation]	Adjusts the saturation of the screen colors. The lower the value, the less saturated and brighter the colors become. The higher the value, saturated and darker the colors become.		
[Picture Reset]	[Do you want to reset your picture settings?]		[No]	Cancel the select.	
			[Yes] Returns to the default settings.		

Sound

[Settings] > [Sound]	Description		
[Volume]	To adjust the Volume of headphone or speaker.		
[MaxxAudio]	[0n]	MaxxAudio® by Waves, recipient of a Technical GRAMMY Award® is a suite of studio-quality sound tools for a superior listening experience.	
[0ff]		Disables the MaxxAudio function.	

General

[Settings] > [General]	Description				
[Language]	Sets the menu screen to the d	Sets the menu screen to the desired language.			
[SMART ENERGY SAVING]	Conserve energy by using lum	Conserve energy by using luminance compensation algorithm.			
	[High]	Saves energy using the high-efficiency [SMART ENERGY SAVING] feature.			
	[Low]	Saves energy using the low-efficiency [SMART ENERGY SAVING] feature.			
	[Off]	Disables the feature.			
 NOTE The value of energy saving data may differ depending on panel and panel suppliers. If you select the option of [SMART ENERGY SAVING] is [High] or [Low], monitor luminance become lower or higher depend on source. 					
[Deep Sleep Mode]	When Deep sleep mode is enabled, power consumption is minimized while the monitor is in standby mode.				
	[0n]	Enables Deep sleep Mode.			
	[0ff]	Disables Deep sleep Mode.			
	NOTE USB HUB functions will not	work in standby mode while Deep sleep Mode is enabled in standby mode.			
[Power LED]	 NOTE When the Power LED function is turned on, it operates as follows: On Mode: White Sleep Mode (Standby Mode): White Blinking Off Mode: Off 				
[Automatic Standby]	Feature that automatically tu	rns off the monitor when there is no movement on the screen for a period of time. You can set a timer for the auto-off function. ([8H], [6H], [4H], and [Off])			

[Settings] > [General]	Description				
[Input Compatibility Version]	Please set the Input Compatibility Versi	the Input Compatibility Version to match the version of the connected external device.			
	[HDMI]	2.1(PC)/2.1(AV)/1.4 If you want to use the HDR, select the Input Compatibility Version to 2.1(PC) or 2.1(AV).			
	[DisplayPort]	1.4(DSC)/1.4/1.2 If you want to use the HDR, select the Input Compatibility Version to 1.4(DSC) or 1.4.			
[Buzzer]	This feature lets you set the sound generated from [Buzzer] when your monitor powers on to [0n] or [Off].				
[OSD Lock]	This feature disables the configuration and adjustment of menus.				
[Information]	The following display information will be shown; [Total Power On Time], [Resolution].				
[Reset to Initial Settings]	[Do you want to reset your settings?]	[No] Cancel the reset.			
	[Yes] Returns to the default settings.				

TROUBLESHOOTING

Nothing is displayed on the screen.				
Is the monitor's power cord plugged in?	Check if the power cord is correctly plugged into the power outlet.			
Is the power LED on?	Check the power cable connection and press the power button.			
Is the power on and the power LED displaying white?	Check that the connected input is enabled ([Settings] > [Input]).			
Is the [No Signal] message being displayed?	• This is displayed when the signal cable between the PC and the monitor is missing or disconnected. Check the cable and reconnect it.			
Is the [Out of Range] message being displayed?	• This occurs when signals transferred from the PC (graphics card) are out of the horizontal or vertical frequency range of the monitor. Please see the Product Specification section of this manual to set the appropriate frequency.			
Screen display is unstable and shaky. / Images displayed on the	e monitor leave shadow trails.			
Did you select the appropriate resolution?	 If the selected resolution is HDMI 1080i 60/50 Hz (interlaced), the screen may be flickering. Change the resolution to 1080p or the recommended resolution. 			
	 Not setting the graphics card to the recommended (optimal) resolution may result in blurred text, a dimmed screen, a truncated display area or misalignment of the display. 			
	 The setting methods may be different depending on the computer or operating system, and some resolutions may not be available depending on the performance of the graphics card. If this is the case, contact the manufacturer of the computer or graphics card for assistance. 			
Does image sticking occur even when the monitor is turned off?	 Displaying a still image for a prolonged time may cause damage to the screen, resulting in the retention of the image. To extend the lifetime of the monitor, use a screensaver. 			
Are there spots on the screen?	• When using the monitor, pixilated spots (red, green, blue, white, or black) may appear on the screen. This is normal for an LCD screen. It is not an error, nor is it related to the monitor's performance.			
Some features are disabled.				
Are some functions not available when you press the Menu button?	The OSD is locked. Disable [OSD Lock] in [General].			

Do you see an "Unrecognized monitor, Plug and Play (Do you see an "Unrecognized monitor, Plug and Play (VESA DDC) monitor found" message?			
Have you installed the display driver?	Have you installed the display driver? • Be sure to install the display driver from our web site: http://www.lg.com. • Make sure to check if the graphics card supports Plug and Play function.			
No sound from the headphone port.	No sound from the headphone port.			
Are images displayed without sound? Make sure that the headphone port connections are made properly. Try increasing the volume with the joystick. Set the audio output of the PC to the monitor you are using. (The settings may differ depending on the operating system (0S) you use.) 				

PRODUCT SPECIFICATION

Color Depth	8-bit/10-bit color is supported.			
Resolution	Max Resolution	3840 x 2160 @ 144 Hz (HDMI / DP) 3840 x 2160 @ 60 Hz (USB-C)		
	Recommended Resolution 3840 x 2160 @ 144 Hz (HDMI / DP) 3840 x 2160 @ 60 Hz (USB-C)			
Power Sources	Power Rating	19.5 V 10.0 A		
	Power Consumption (Typical)	On mode: 85 W Typ. (Outgoing condition)* Sleep Mode (Standby Mode) ≤ 0.5 W (HDMI / DP input Condition)** Off Mode ≤ 0.3 W		
AC/DC Adapter	ACC-LATP2 type, manufactured by SHE Input: 100-240 V ~50/60 Hz 2.5A Output: 19.5 V 10.8 A	NZHEN HONOR ELECTRONIC CO., LTD		
Environmental Conditions	Operating Conditions	Temperature	0 °C to 40 °C (32 °F to 104 °F)	
		Humidity	Less than 80 %	
	Storing Conditions	Temperature	-20 °C to 60 °C (-4 °F to	o 140 °F)
		Humidity	Less than 85 %	
Dimensions	Monitor Size (Width x Height x Depth)		• 	
With Stand 714.3 x 597.6 x 239.3 (mm) 28.1 x 23.5 x 9.4 (inches)		28.1 x 23.5 x 9.4 (inches)		
	Without Stand	714.3 x 420 x 45.7 (mm) 28.1 x 16.5 x 1.7 (inches)		28.1 x 16.5 x 1.7 (inches)
Weight (Without Packaging)	With Stand	8.7 (kg)	19.1 (lbs) 14.9 (lbs)	
	Without Stand	6.8 (kg)		

The specifications are subject to change without notice.

The ~ symbol means alternating current, and the _____ symbol means direct current.

The power consumption level can be different by operating condition and monitor setting.

* The On mode power consumption is measured with LGE test standard (Full White pattern , Maximum resolution).

** In case of USB-C input, the power consumption of Sleep Mode may vary depending on the connected device.

** The monitor goes to the Sleep Mode in a couple of minutes(Max 5 minutes).

Factory Support Mode (Preset Mode, PC)

USB-C/DisplayPort

Preset Mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1920 x 1080	66.59	59.93	+/-	USB-C
1920 x 1080	67.5	60	+/+	DisplayPort
1920 x 1080	166.587	143.98	+/-	DisplayPort
2560 x 1440	88.79	59.95	+/-	USB-C
2560 x 1440	222.151	143.97	+/-	DisplayPort
3840 x 2160	67.5	30	+/+	USB-C
3840 x 2160	133.31	60	+/-	
3840 x 2160	214.563	94.98	+/-	DisplayPort
3840 x 2160	268.44	120	+/-	DisplayPort (Input Compatibility Version 1.4)
3840 x 2160	332.06	144	+/-	DisplayPort

ш	n	A	A 1
п	υ	N	ш

Preset Mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)	Polarity (H/V)	Remarks
640 x 480	31.469	59.94	-/-	
800 x 600	37.879	60.317	+/+	
1024 x 768	48.363	60	-/-	
1920 x 1080	67.5	60	+/+	
1920 x 1080	166.587	143.98	+/-	
2560 x 1440	182.996	120	+/-	
2560 x 1440	222.151	143.97	+/-	
3840 x 2160	67.5	30	+/+	
3840 x 2160	135	60	+/+	
3840 x 2160	332.06	144	+/-	

HDMI Timing (Video)

Preset Mode	Horizontal Frequency (kHz)	Vertical Frequency (Hz)
480P	31.5	60
576P	31.25	50
720P	37.5	50
720P	45	60
1080P	27	24
1080P	33.75	30
1080P	56.25	50
1080P	67.5	60
1080P	135	120
2160P	54	24
2160P	56.25	25
2160P	67.5	30
2160P	112.5	50
2160p	135	60
2160P	270	120

Beep Guide

Menu	Location
Quick Settings	1
Quick Settings - Brightness	11
Quick Settings - Brightness	1 1 1 Slider
Quick Settings - Contrast	12
Quick Settings - Contrast	1 2 1 Slider
Quick Settings - Volume	13
Quick Settings - Volume	1 3 1 Slider
Quick Settings - Color Temp	14
Quick Settings - Color Temp - Custom	141
Quick Settings - Color Temp - Warm	142
Quick Settings - Color Temp - Medium	143
Quick Settings - Color Temp - Cool	144
Quick Settings - Color Temp - Manual	145
Quick Settings - Color Temp - Manual	1451Slider
Quick Settings - Waves MaxxAudio	1 5 Toggle
Input	2
Input - Input List	21
Input - Input List - HDMI 1	211
Input - Input List - HDMI 2	212
Input - Input List - DisplayPort	213
Input - Input List - USB-C	214
Input - Aspect Ratio	22
Input - Aspect Ratio - Full Wide	221
Input - Aspect Ratio - Original	222
Input - Aspect Ratio - Just Scan	223

Menu	Location
Picture	3
Picture - Picture Mode	31
Picture - Picture Mode - Custom	311
Picture - Picture Mode - Vivid	312
Picture - Picture Mode - HDR Effect	313
Picture - Picture Mode - Reader	314
Picture - Picture Mode - Cinema	315
Picture - Picture Mode - sRGB	316
Picture - Picture Mode - DCI-P3	317
Picture - Picture Mode - FPS	318
Picture - Picture Mode - RTS	319
Picture - Picture Mode - Color Weakness	3 1 10
Picture - Picture Adjust	32
Picture - Picture Adjust - Brightness	321
Picture - Picture Adjust - Brightness	3 2 1 1 Slider
Picture - Picture Adjust - Contrast	322
Picture - Picture Adjust - Contrast	3 2 2 1 Slider
Picture - Picture Adjust - Sharpness	323
Picture - Picture Adjust - Sharpness	3 2 3 1 Slider
Picture - Picture Adjust - SUPER RESOLUTION+	324
Picture - Picture Adjust - SUPER RESOLUTION+ - High	3241
Picture - Picture Adjust - SUPER RESOLUTION+ - Middle	3242
Picture - Picture Adjust - SUPER RESOLUTION+ - Low	3243
Picture - Picture Adjust - SUPER RESOLUTION+ - Off	3244
Picture - Picture Adjust - Black Level	325

Menu	Location
Picture - Picture Adjust - Black Level - High	3251
Picture - Picture Adjust - Black Level - Low	3252
Picture - Picture Adjust - DFC	3 2 6 Toggle
Picture - Game Adjust - Response Time	331
Picture - Game Adjust - Response Time - Faster	3311
Picture - Game Adjust - Response Time - Fast	3312
Picture - Game Adjust - Response Time - Normal	3313
Picture - Game Adjust - Response Time - Off	3314
Picture - Game Adjust - Adaptive-Sync (HDMI : VRR)	332
Picture - Game Adjust - Adaptive-Sync (HDMI : VRR) - Extended	3321
Picture - Game Adjust - Adaptive-Sync (HDMI : VRR) - Basic	3322
Picture - Game Adjust - Adaptive-Sync (HDMI : VRR) - Off	3323
Picture - Game Adjust - Black Stabilizer	333
Picture - Game Adjust - Black Stabilizer	3 3 3 1 Slider
Picture - Color Adjust - Gamma	3 4 1
Picture - Color Adjust - Gamma - Mode 1	3411
Picture - Color Adjust - Gamma - Mode 2	3412
Picture - Color Adjust - Gamma - Mode 3	3413
Picture - Color Adjust - Gamma - Mode 4	3414
Picture - Color Adjust - Color Temp	3 4 2
Picture - Color Adjust - Color Temp - Custom	3421
Picture - Color Adjust - Color Temp - Warm	3422
Picture - Color Adjust - Color Temp - Medium	3423

Mellu	Location
Picture - Color Adjust - Color Temp - Cool	3424
Picture - Color Adjust - Color Temp - Manual	3425
Picture - Color Adjust - Color Temp - Manual	3 4 2 5 1 Slider
Picture - Color Adjust - Red	3 4 3
Picture - Color Adjust - Red	3 4 3 1 Slider
Picture - Color Adjust - Green	344
Picture - Color Adjust - Green	3 4 4 1 Slider
Picture - Color Adjust - Blue	3 4 5
Picture - Color Adjust - Blue	3 4 5 1 Slider
Picture - Color Adjust - Six Color	346
Picture - Color Adjust - Six Color - Red_Hue	3461
Picture - Color Adjust - Six Color - Red_Hue	3 4 6 1 1 Slider
Picture - Color Adjust - Six Color - Red_Saturation	3462
Picture - Color Adjust - Six Color - Red_Saturation	3 4 6 2 1 Slider
Picture - Color Adjust - Six Color - Green_Hue	3463
Picture - Color Adjust - Six Color - Green_Hue	3 4 6 3 1 Slider
Picture - Color Adjust - Six Color - Green_Saturation	3464
Picture - Color Adjust - Six Color - Green_Saturation	3 4 6 4 1 Slider
Picture - Color Adjust - Six Color - Blue_Hue	3465
Picture - Color Adjust - Six Color - Blue_Hue	3 4 6 5 1 Slider
Picture - Color Adjust - Six Color - Blue_Saturation	3466
Picture - Color Adjust - Six Color - Blue_Saturation	3 4 6 6 1 Slider

Menu

Location

Menu	Location
Picture - Color Adjust - Six Color - Cyan_Hue	3467
Picture - Color Adjust - Six Color - Cyan_Hue	3 4 6 7 1 Slider
Picture - Color Adjust - Six Color - Cyan_Saturation	3468
Picture - Color Adjust - Six Color - Cyan_Saturation	3 4 6 8 1 Slider
Picture - Color Adjust - Six Color - Magenta_Hue	3469
Picture - Color Adjust - Six Color - Magenta_Hue	3 4 6 9 1 Slider
Picture - Color Adjust - Six Color - Magenta_Saturation	34610
Picture - Color Adjust - Six Color - Magenta_Saturation	3 4 6 10 1 Slider
Picture - Color Adjust - Six Color - Yellow_Hue	34611
Picture - Color Adjust - Six Color - Yellow_Hue	3 4 6 11 1 Slider
Picture - Color Adjust - Six Color - Yellow_Saturation	34612
Picture - Color Adjust - Six Color - Yellow_Saturation	3 4 6 12 1 Slider
Picture - Picture Reset - No	351
Picture - Picture Reset - Yes	3 5 2
Sound	4
Sound - Volume	41
Sound - Volume	411Slider
Sound - Waves MaxxAudio	4 2 Toggle
General	5
General - Language	51
General - Language - English	511
General - Language - German	512

Menu	Location
General - Language - French	513
General - Language - Spanish	514
General - Language - Italian	515
General - Language - Swedish	516
General - Language - Finnish	517
General - Language - Portuguese	518
General - Language - Portuguese (Brazil)	519
General - Language - Polish	5 1 10
General - Language - Russian	5 1 11
General - Language - Greek	5 1 12
General - Language - Ukrainian	5 1 13
General - Language - Chinese	5 1 14
General - Language - Traditional Chinese	5 1 15
General - Language - Japanese	5 1 16
General - Language - Korean	5 1 17
General - SMART ENERGY SAVING	5 2
General - SMART ENERGY SAVING - High	521
General - SMART ENERGY SAVING - Low	522
General - SMART ENERGY SAVING - Off	523
General - Deep Sleep Mode	5 3 Toggle
General - Power LED	5 4 Toggle
General - Automatic Standby	5 5
General - Automatic Standby - 8H	551
General - Automatic Standby - 6H	552
General - Automatic Standby - 4H	553
General - Automatic Standby - Off	554

Menu	Location
General - Input Compatibility Version	56
General - Input Compatibility Version - 1.4(DSC) / 2.1(PC)	561
General - Input Compatibility Version - 1.4 / 2.1(AV)	562
General - Input Compatibility Version - 1.2 / 1.4	563
General - Buzzer	5 7 Toggle
General - OSD Lock	5 8 Toggle
General - Information	59
General - Information	591
General - Reset to Initial Setting	5 10
General - Reset to Initial Setting - No	5 10 1
General - Reset to Initial Setting - Yes	5 10 2



Supplier's Declaration of Conformity		
Trade Name	LG	
Responsible Party	LG Electronics USA, Inc.	
Address	111 Sylvan Avenue, North Building,	
	Englewood Cliffs, NJ 07632	
E-mail	lg.environmental@lge.com	

The model and serial number of the product are located on the back and on one side of the product. Record them below in case you ever need service.

Model

Serial No.